

SOLID OAK FLOORING QUALITY DESCRIPTION

Technical parameters

Tongue & groove and bevels all 4 sides.

Surface could be brushed, weathered, oiled, or lacquered. For indoor use only.

Wood species: European Oak (*Quercus petraea*)

Dimensions

Thickness: 20 mm

Width: 180 mm

Mixed lengths: $\geq 80\%$ 1400-2500 mm, $\leq 20\%$ iki 1400 mm

Allowed tolerances:

Width ± 0.6 mm

Lipping (between elements) ± 0.3 mm

Relative wood humidity (RH) in stock $8\% \pm 3\%$

GRADE

RUSTIC

Allowed characteristics:

- Sound or cracked filled knots \varnothing up to 65 mm
- Filled knotholes \varnothing up to 35 mm
- Filled cracks
- Occasional sapwood or heartwood
- Changes in wood grain

Woodworm, mechanical defects, and mold are not allowed.



The knot filler changes colour when oiled. It absorbs the oil and pigment and adapts to the colour of the flooring. However, the knot filler does not change colour when lacquered.

Colour: Due to natural changes in wood grain and chemical structure, the colour of the product may differ slightly from the showroom samples.

We will not take responsibility for the flooring defects which occur due to incorrect storage, installation, maintenance, or other factors which are not caused by the producer.

For general guidelines on proper storage, installation and maintenance, please visit <http://www.brolistimber.eu/grindys/kolekcija-brolio-paprastumas/medzio-masyvo-grindys/> or contact BROLIS TIMBER.

VilniujeAukštaičių g. 10
LT-11341
+370 640 17 000**Kaune**Nemajūnų g. 25A
LT-52449
+370 640 58 000**Klaipėdoje**Danės g. 21-26
LT-92111
+370 699 98 419